
R. A. Ross saves sewer utility hundreds on lift station grinder pumps.



Solutions like this are what we do every day at R. A. Ross.





- GF series model 32GF22.2:
 44 GPM @ 108' TDH max
- 1.25" NPT discharge w/elbow
- · Semi-open impeller
- 55-60 Rockwell C hardness cutter and cutter ring
- FC 200 cast-iron construction
- 316SS hardware
- 3-HP, 230-460/3/60 motor
- 30' control cable
- Double mechanical seal Lower - carbon ceramic
 Upper - silicon carbide/silicon carbide

Tough applications and regulations are right up our alley

SITUATION:

When a rural sewer utility came to us looking for a more economical grinder pump for their sewage lift stations, we had the exact solution; the HCP, GF Series grinder pump which was a "drop in" replacement for the competitors pump the customer had been using. In addition to matched performance and ease of installation, the HCP pump was over \$500 less expensive than the competition. The customer is so satisfied with the price and performance of the HCP pumps, they are replacing the competitors pumps one by one as they go bad. The first HCP pump installed has been running for two years now with no issues. HCP Pumps America manufactures a wide range of submersible pumps from fractional HP to 250-HP for just about any dewatering or sewage application.

Give us a call and let us find a solution for you!

HCP is your one stop shop for submersible pumps of all kinds, shapes and sizes with pumps to at least 250 HP. HCP also offers grinder pumps and even down hole well pumps.



SUMP PUMPS (A Series) 1/2-3 HP to 290 GPM to 100' TDH Wastewater Sump 2" & 3" discharge

DEWATERING (ASH & AH Series)

11/2-10 HP to 215 GPM to 135' TDH SS w/hi-chrome hard impleller 2"-6" discharge

LARGE VOLUME DEWATERING (L Series) 1/2-20 HP TO 2640 GPM TO 20' TDH 3"-12" discharge, _____ & mixed flow

EFFLUENT (F Series) 1/2-10 HP to 520 GPM 132' TDH 2"-4" discharge

GRINDERS (GF Series)

1.25-5 HP to 88 GPM to 120' TDH 11/4"-2" discharge

SEWAGE/WASTEWATER (AF & IF Series)

1/2-250 HP to 148' TDH to 8206 GPM 2" to 16" discharge 4" solids

CUTTER PUMPS (WASTEWATER/SEWAGE) (AFC Series) 2-3 HP to 63' TDH 3" to 291 GPM

SLURRY PUMPS/DEWATERING PUMPS (SAND & GRAVEL, COAL PLANTS, CONSTRUCTION)

(AG & AFG Series) 2-15 HP to 125' TDH to 687 GPM 3"-6" discharge

AXIAL FLOW (LA Series)

50-200 HP to 24' TDH to 42,800 GPM 22" to 28" discharge

STAINLESS STEEL (S Series) 1/2-5 HP to 72' TDH to 290 GPM 2" to 3" discharge

JET PUMPS (JF, JP & GRS Series) **EJECTOR PUMPS ADDS AIR TO LIQUID**

to 10 HP to 1.8' TDH to 555 GPM

SUCTION LIFT SELF PRIMING NON-CLOG

2" to 12" to 125 HP to 2065' TDH to 5500 GPM

MIXERS (COMING SOON)

MAKO SERIES SUBMERSABLE WELL PUMPS

304 SS to 155 HP to 1,378' to 660 GPM 5" to 8" discharge

PANELS: ENGINEERED CUSTOM, STD LIFT STATION CONTROLS

ACCESSORIES

- · Guide rail systems
- · Float switch
- · Flange/Flange set
- Outlet set
- Adapters
- Supplements
- Basins

CONTACT US

Call us for information on how we can help solve your problems in any of the following areas:

- Pumps
- **Blowers**
- **Filters**
- **Mixers**
- **Tanks**
- Vacuum Pumps
- **Mechanical Seals**
- **Heat Exchangers**
- Repairs



Keeping process flowing since 1985

R. A. Ross & Associates, Inc. Headquarters 2231-A Ampere Drive Louisville, KY 40299

502 267-8677 Fax 502 266-7928 1 800-489-8677 solutions@raross.com www.raross.com

Serving Kentucky, Indiana, Ohio and W. Virginia





